

COPY

- 1 -

COPY

TITLE OF THE INVENTION

METHOD AND APPARATUS FOR MANUFACTURING A SEMICONDUCTOR
DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Applications No. 11-139820, filed May 20, 1999;
No. 11-228521, filed August 12, 1999; and No. 11-280266,
filed September 30, 1999, the entire contents of which
10 are incorporated herein by reference.

BACKGROUND OF THE INVENTION

 The present invention relates to a method and
apparatus for manufacturing a semiconductor device made
by forming a thin film on a substrate, such as a thin-
15 film photovoltaic module.

 To manufacture a thin-film photovoltaic module,
for example, a thin film such as a semiconductor film
or a metal film is formed on a substrate made of glass
and having a transparent electrode formed on it.

20 When the thin film is formed on the substrate,
particles may be attached to the substrate. If this
happens, defects will develop. Therefore, the
substrate is usually washed before the thin film is
formed on the substrate in order to remove the
25 particles.

 When the washed substrate is left to stand and is
thereby dried, the washing liquid attached to the

substrate may form a water mark (stain). The substrate is therefore forcibly dried after the washing.

To dry the washed substrate, a clean oven is used in a conventional method. The clean oven is designed
5 such that clean air is introduced into the interior. In the clean oven, the air is heated by a heater and circulated.

Therefore, if the washed substrate is placed in the clean oven, it can be dried with the heated air
10 circulating in the clean oven.

As indicated above, the clean oven is designed to dry the substrate while the heated air is circulated, oven is clean, hence, the air gradually contain with particles remaining in the clean oven even if it is
15 clean when introduced into the clean oven.

It is therefore easy for particles to attach to the substrate dried in the clean oven. Consequently, defects are likely to develop in the thin film formed on the substrate.

20 BRIEF SUMMARY OF THE INVENTION

An object of the present invention is to provide a method and apparatus for manufacturing a semiconductor device, characterized in that a washed substrate is free of contamination while it is being dried.

25 To achieve the object, a method of manufacturing a semiconductor device, wherein a thin film is formed on a substrate, comprises the steps of:

(a) washing the substrate with a washing liquid;
(b) removing the washing liquid from the substrate
by blowing a compressed air to the substrate washed;
and

5 (c) forming a thin film on the substrate
immediately after the step (b), without performing to
another step.

In the method, the substrate is dried with clean
air by blowing compressed air to the substrate.
10 Contamination of the substrate can be prevented in the
drying process.

Other objects and advantages of the present
invention will become apparent from a consideration of
the following Detailed Description of the Invention.
15 The objects and advantages of the present invention can
be attained by the constitutions clearly set forth in
the accompanying claims or combination of the
constitutions.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING
20 The accompanying drawings, which are incorporated
in and constitute a part of the specification,
illustrate presently preferred embodiments of the
invention, and together with the general description
given above and the detailed description of the
25 preferred embodiments given below, serve to explain the
principles of the invention.

FIG. 1 is a view showing an apparatus for

manufacturing a semiconductor device, according to a first embodiment of the present invention;

FIG. 2 is a schematic view showing the washing section of the apparatus;

5 FIG. 3 is a schematic plan view of the liquid removing section of the apparatus;

FIG. 4 is a side view of the liquid removing section;

10 FIG. 5 is a schematic view of the film forming section of the apparatus;

FIG. 6 is a cross sectional view of the substrate having a thin film subjected to scribing;

FIG. 7 is a schematic side view of a washing unit according to a second embodiment of the invention;

15 FIG. 8 is an enlarged view of part A of FIG. 7;

FIG. 9 is a schematic perspective view of the air blower mechanism of the washing unit;

FIG. 10 is a schematic perspective view of an air blower mechanism according to a third embodiment of the invention;

20 FIG. 11 is a plan view of a liquid removing section according to a fourth embodiment of the present invention; and

25 FIG. 12 is a side view of the liquid removing section.

DETAILED DESCRIPTION OF THE INVENTION

Embodiments of the present invention will be

described with reference to the accompanying drawings.

FIG. 1 shows an apparatus of manufacturing a semiconductor device, which is the first embodiment of the invention. The apparatus has a washing section 1, a liquid-removing section 2, and a film forming section 3.

The washing section 1 is designed to wash a glass substrate 10 having a transparent conducting film formed thereon and used as an electrode film, as shown in FIGS. 2, 3 and 4. The substrate 10 is a component of a semiconductor device, more precisely a thin film type photovoltaic module. The substrate is washed in the washing section 1 and dried in the liquid removing-section 2. Thereafter, a thin film, such as a semiconductor film or a metal film, is formed on that surface of the substrate on which an electrode film is provided (hereinafter, referred to as "upper surface"), in the film forming section 3.

As shown in FIGS. 2 and 3, a transfer mechanism 5 is provided in the washing section 1 and the liquid removing-section 2. The transfer mechanism 5 comprises a plurality of transfer rollers 4. The transfer mechanism 5 transfers the substrate 10 from the washing section 1 to the liquid removing section 2.

As shown in FIG. 2, the washing section 1 comprises a brush washing section 6, a rinse section 7, and an ultrasonic washing section 8. The sections 6, 7,

and 8 are arranged in the direction of transferring the substrate 10.

5 The brush washing section 6 has a pair of washing brushes 9 and a nozzle body 11. The brushes 9 in contact the upper and lower surfaces of the substrate 10, respectively, which is to be transferred by the transfer roller 4. The nozzle body 11 supplies washing liquid such as detergent or pure water to a position where the washing brushes 9 contact the substrate 10.

10 The upper surface of the substrate 10 is brush-washed with the washing liquid.

The nozzle body 11 is a tube 11a longer than the width of the substrate 10. The tube 11a has a plurality of nozzle holes 11b arranged at predetermined intervals.

15

In this embodiment, the washing liquid is supplied by the nozzle body 11 to only both upper and lower surfaces of the substrate 10 on which the thin film is to be formed. Nevertheless, the nozzle body 11 may be located only above the substrate 10 to wash the upper surface only.

20

The rinse section 7 has a rinse vessel 12. The rinse vessel 12 has a loading port 13 and an unloading port 14, the loading port 13 is made in the side wall positioned at the upstream of the transfer path of the substrate 10. The unloading port 14 is made in the opposite side wall positioned at the downstream of the

25

transfer path. The loading port 13 and the unloading port 14 are formed at almost the same level as that of the substrate 10 to be transferred by the transfer roller 4.

5 Within the rinse vessel 12, the transfer roller 4 constituting the transfer mechanism 5 is arranged at the same level as that of the transfer roller 4 arranged outside. The mechanism 5 can transfer the substrate 10 through the loading port 13 into the rinse
10 vessel 12 and from the vessel 12 through the unloading port 14, as shown by arrows in FIGS. 1 and 2.

 Into the rinse vessel 12 rinse liquid such as pure water is supplied by the supply nozzle (not shown). The rinse liquid flows out of the rinse vessel 12
15 through the loading port 13 and the unloading port 14. The rinse liquid is supplies into the rinse vessel 12 at a rate equal to or slightly higher than the rate at which the liquid blows out through the loading port 13 and the unloading port 14.

20 With this mechanism, the surface of the rinse liquid in the rinse vessel 12 can be maintained at a higher level than the substrate 10. Thus, the substrate 10 is transferred in the rinse liquid. Therefore, the upper surface of the substrate 10
25 passing through the rinse vessel 12 is rinsed with the rinse liquid without fail. Furthermore, the particles washed out from the substrate 10 by the rinse treatment

are rarely left in the rinse vessel 12. This is because the rinse liquid is always allowed to flow out from the loading port 13 and the unloading port 14.

In this embodiment, a single rinse vessel is used. Nevertheless, a plurality of rinse vessels may be arranged in the transfer direction of the substrate 10 to rinse more reliably the substrate 10 washed with the washing liquid.

The substrate 10 rinsed in the vessel 12 is washed in the ultrasonic washing section 8 having a washing vessel 15. The washing vessel 15 has a loading port 16 made in the side wall positioned at the upstream of the transfer path of the substrate 10. The vessel 15 has an unloading port 17 made in the opposite side wall positioned at the downstream of the transfer path. Both ports 16 and 17 are at substantially the same level as the substrate 10 to be transferred.

Inside the washing vessel 15, the transfer rollers 4 are arranged in the same manner as in the rinse vessel 12. An ultrasonic generator 18 for generating an ultrasonic vibration of about 20-40 kHz is provided at the bottom portion. Pure water is supplied into the washing vessel 15 as the washing liquid. The ultrasonic vibration generated by the ultrasonic wave generator 18 is applied to the washing liquid.

The rate of supplying the washing liquid is almost equal to or slightly larger than the rate at which the

liquid flows out through the loading port 16 and unloading port 17. As mentioned above, the surface of the washing liquid in the washing vessel 15 is slightly higher than the upper surface of the substrate 10 to be transferred by the transfer rollers 4. Therefore, both upper and lower surfaces of the substrate 10 can be washed by the washing liquid vibrated by the ultrasonic wave.

In addition, since a part of the washing liquid flows from the loading port 16 and the unloading port 17, the particles removed from the substrate 10 by the ultrasonic washing can flow out, too.

The substrate 10 washed in the ultrasonic washing section 8 is dried in the liquid-removing section 2 shown in FIGS. 3 and 4. The solution-removing section 2 is constituted of a pair of air knives 21 which face the upper and lower surfaces of the substrate to be transferred. To the air knife 21, compressed air cleaned by a filter is applied through a pipe 19.

Onto the pipe 19, there are provided a heater 20 for heating the compressed air and an ionizing portion 23 for ionizing the compressed air. Note the compressed air is set at a pressure of about 5 kg/cm^2 by a pressure control valve 24 attached to the pipe 19. The air knives 21 are longer than the width of the substrate 10. As shown in FIGS. 3 and 4, each air knife 21 has a slit 22 extending along almost all

length of the knife and opening at an edge thereof.
The slits 22 of the air knives 21 face the upper or lower surface of the substrate 10, respectively.

Each air knife 21 is inclined at a predetermined
5 angle α to the transfer direction X of the substrate.
The compressed air is applied through the slit 22 in a direction Z inclined at an angle β to the direction V perpendicular to the transfer direction X, as shown in FIG. 3.

10 The compressed the air applied to each air knife 21 is blown toward the upper or lower surface of the substrate 10 from the slit hole 22. The washing liquid on the upper and lower surfaces of the substrate 10 is thereby pushed toward the rear edge of the substrate 10
15 in the transfer direction of the substrate, as indicated by an arrow Y in FIG. 3. As a result, the washing liquid falls dropwise and smoothly from the end of the substrate. Thus, the washing liquid is removed from the substrate 10.

20 The compressed air to apply to the air knife is heated by the heater 20 to a temperature higher than room temperature, for example, to about 40-50°C
Therefore, the washing liquid is removed from the substrate 10 by force of the compressed air, and the
25 substrate 10 is dried with heat of the compressed air.
Therefore, the substrate 10 can be efficiently dried without fail.

Even if the compressed air is not heated, the substrate can be dried to a predetermined degree. On the other hand, if the compressed air is ionized and applied to the substrate 10, the substrate 10 can be prevented from being electrically charged during the drying process. As a result, no static electricity will be generated, no particles will be attached to the substrate 10. Hence, the substrate 10 is not contaminated during the drying process.

The substrate 10 dried in the solution-removing section 2 is immediately transferred to the film forming section 3. More specifically, the substrate 10 is unloaded by the transfer rollers 4 and transferred to the film forming section 3 by a robot (not shown). In other words, the substrate 10, from which the washing liquid has been removed, is directly transferred to the film forming section 3 without being subjected to any other process.

The substrate 10 dried in the liquid removing section 2 and unloaded therefrom is continuously loaded into the film forming section 3. Therefore, the chance for the particles in the atmosphere to attach to the dried substrate 10 are small. The substrate 10 is transferred to the film forming process 3, while kept clean.

Furthermore, the substrate 10 is dried with the compressed air, not in a clean oven as in the

conventional method. The drying process can therefore be performed immediately after the washing process.

Therefore, unlike the case where the washed substrates 10 are dried in batches in a clean oven, the time elapsing between the washing process and the drying process can be reduced. It is therefore possible to prevent the washing liquid applied to the substrate 10 during the washing process, from partially being dried before the dry process to make a water mark (stain) onto the substrate 10.

The film forming section 3 has a film forming chamber 25 as shown in FIG. 5. The film forming chamber 25 is used for forming a thin film on the upper surface of the substrate 10 by a plasma process (CVD). The film forming chamber 25 has a loading port 26 in one side and an unloading port 27 in the opposite side. Provided in the film forming chamber 25 are a table 28 and a high frequency electrode 29. The table 28 incorporates a heater 28a. The electrode 29 is arranged, facing the upper surface of the table 28.

Furthermore, two supply pipes 31 and 32 are connected to the upper portion of the film forming chamber 25. The first supply pipe 31 is used to supplies material gas. The second supply pipe 32 is provided for supplying an inert gas into the film formation chamber 25. To the bottom of the chamber 25, an exhaust pipe 34 having a vacuum pump 33 is connected.

At the loading port 26 of the film forming chamber 25, a load-lock chamber 35 is arranged. At the unloading port 27 of the chamber 25, an unload-lock chamber 36 is arranged. The chambers 35 and 36 have loading ports 35a and 36a and unloading ports 35b and 36b, respectively.

A pre-heater 37 and a support table 38 are arranged in the load-lock chamber 35. An exhaust duct 40 having a vacuum pump 39 is connected to the bottom of the load-lock chamber 35.

The unloading port 35b of the load-lock chamber 35 and the loading port 26 of the film forming chamber 25 are connected airtight by a first connecting body 41. The unloading port 27 of the film forming chamber 25 and the loading port 36a of the unload-lock chamber 36 are connected airtight by way of a second connection body 42.

The loading ports and the unloading ports of the chambers 25, 35 and 36 are closed airtight by valves 43. The first and second connecting bodies 41 and 42 incorporate transfer robots (not shown). Furthermore, a mounting table 44 is arranged in the unload-lock chamber 36. An exhaust duct 46 having an vacuum pump 45 is connected to the bottom of the chamber 36.

When the substrate 10 dried in the liquid removing section 2 is placed on the support table 38 in the load-lock chamber 35, the loading port 35a is closed

and the load-lock chamber 35 is depressurized. Simultaneously, the substrate 10 is pre-heated by the pre-heater 37. During the preheating, the load-lock chamber 38 is depressurized by the vacuum pump 39.

5 When the substrate 10 is pre-heated, the loading port 35a of the load-lock chamber 38 is closed and the unloading port 35b is opened. Subsequently, the robot arranged in the first connecting body 41 enters the load-lock chamber 35 and receives the substrate 10 from
10 the holding table 38.

 At the same time, the unloading port 35b of the load-lock chamber 35 is closed airtight by the valve 43. Simultaneously, the loading port 26 of the film forming chamber 25 is opened. The substrate 10 preheated is
15 placed onto the table 28 in the film forming chamber 25 by the robot arranged in the first connection body 41. Then, the robot moves back. Thereafter, the loading port 26 is closed, and the film formation chamber is depressurized by the vacuum pump 33.

20 When the film forming chamber 25 is depressurized to a predetermined pressure, an inert gas is supplied from the second supply pipe 32 into the chamber 25. Simultaneously, high frequency power is supplied to a high frequency electrode 29, activating the inert gas.
25 The gas activated has a cleaning function. The substrate 10 washed in the washing section 1 is therefore further cleaned with the inert gas.

When the substrate 10 is cleaned with the inert gas for a predetermined time, material gas is supplied, in place of the insert gas, from the first supply pipe 31 into the film forming chamber 25. The material gas is reacted in a plasma generated by supplying a high frequency power to the high frequency electrode 29.

As a result, a solid substance generated in the reaction is deposited on the upper surface of the substrate 10, forming a thin film on the upper surface of the substrate 10.

The substrate 10 is washed in the washing section 1 and then transferred to the solution-removing section 2, in which the substrate 10 is dried without contamination. Thereafter, the substrate 10 is transferred to the film forming chamber 25.

Since no particles are contained in the thin film deposited on the substrate 10, it is possible to prevent defects from developing in the thin film. As a result, the semiconductor device can be manufactured in a high yield.

In the case of a photovoltaic module having 50 cells connected in series, manufactured by employing the clean oven in a conventional drying process of the substrate 10, 40 cells are defective as experiments shows. In the case of the photovoltaic module according to the present invention wherein the substrate 10 has been dried with the compressed air,

defects were developed in only 10 or less cells.

To detect whether or not a cell has defects, a reverse voltage is applied to the cell. If the particles are contained in the film during the film forming process, they cause a short circuit. Whether defects have developed or not can be determined in accordance with whether the applied voltage changes or not.

When the film formation on the substrate 10 is completed, the unloading port 27 of the film forming chamber 25 is opened, and a robot moves from the second connecting body 42 and enters the film forming chamber 25 and receives the substrate 10. Simultaneously, the loading port 36a of the unload-lock chamber 36 is opened.

The robot loads the substrate 10, on which a film is formed in the film forming chamber 25, into the unload-lock chamber 36 and mounts it on a mounting table 44. Thereafter, the robot moves back to the second connecting body 42. Simultaneously, the unloading port 27 of the film forming chamber 25 and the loading port 36a of the load-lock chamber 36 are closed.

In this embodiment, the load-lock chamber 35 and unload-lock chamber 36 are connected airtight at the loading port 26 and the unloading port 27 of the film forming chamber 25, respectively. By virtue of this

structural feature, the substrate 10 can be transferred without significantly degrading the depressurized state of the film forming chamber 25.

5 The substrate 10 mounted on the mounting table 44 of the unload-lock chamber 36 is taken out by a robot (not shown) placed outside the unloading port 43 of the chamber 36. The substrate 10 is then subjected to the next process.

10 The present invention is not limited to the aforementioned embodiment. For example, a single brush washing unit, a single rinse unit and a single ultrasonic washing unit, all used in the washing section in the aforementioned embodiment, however, may each be replaced by a plurality of units. Further, the
15 three types of washing units used in combination may be replaced by one or two types of washing units.

20 A nozzle washing unit for applying the ultrasonically vibrated washing liquid from the nozzle to the substrate may be combined with the aforementioned washing units or may be used alone.

25 A single load-lock chamber for preheating the substrate and maintaining the reduced pressure state of the film formation chamber is placed at the upstream of the film formation chamber in the film forming section. Nonetheless, a plurality of load-lock chambers may be used to perform a series of processes on the substrate continuously, without waiting time, if the efficiency

in preheating the substrate is improved and if each of the periods required for the washing section and the liquid removing section is equal to the period required to form the film formation in the film forming section.

5 The semiconductor device of the present invention is not limited to a photovoltaic module. Rather, it may be a liquid crystal display panel and a semiconductor wafer. In short, the present invention can be applied to any case where a thin film is formed
10 on the substrate.

 In the film forming section 3 shown in FIG. 1, a transparent conducting film 51, a semiconductor film 52 for use in photovoltaic conversion, and a rear surface electrode film 53 are stacked on upon another, on the
15 substrate 10 as shown in FIG. 6. When these films are stacked, each of the films are scribed as is indicated by a scribe line 54 in the figure. The scribe lines are formed by a laser beam.

 When the thin film is scribed with the leaser beam,
20 particles of debris are generated. The particles are attached to the substrate 10 and remain thereon. The particles remaining on the substrate 10 sometimes cause defects in the thin film formed next thereon.

 It is necessary to wash the substrate 10 after the
25 transparent conducting film 51 is formed and scribed, after the semiconductor film 52 is formed on the transparent conducting film 51 and scribed, and after

the rear surface electrode 53 is formed and scribed.

FIGS. 7 to 9 show a second embodiment of the present invention. This embodiment is a washing unit for washing the substrate 10 after the transparent conducting film 51 is formed on the substrate 10 and scribed, after the semiconductor film 52 for photovoltaic conversion is formed and scribed, and the rear surface electrode film 53 is formed and scribed.

Now, the washing unit will be explained. FIG. 7 is a schematic vertical longitudinal sectional view of the washing unit for the substrate 10 for a photovoltaic module. FIG. 8 is an enlarged sectional view of portion A of FIG. 7. FIG. 9 is a perspective view of an air blower mechanism.

The washing unit for washing the substrate 10 has a base 111. A washing vessel 112 is provided on the base 111. A loading port 113 for the substrate 10 is made in the side wall at one of the washing vessel 112. The wall at the other end has an unloading port 114. A roller conveyer 115 is provided as a transfer mechanism, both inside and outside the washing vessel 112 at the substantially the same level as the loading port 113 and the unloading port 114. The roller conveyer 115 transports the substrate 10 horizontally. While the substrate 10 is being so transported, its surface, on which a transparent electrode 51 is formed, remains turned upward.

The rollers 115a constituting the roller conveyer 115 are rotated by a rotation-drive mechanism (not shown). With this rotation, the substrate 10 is loaded into the washing vessel 112 through the loading port 113 and unloaded through the unloading port 114.

A loading section 116 is provided at the loading port 113 of the washing vessel 112, for loading the substrate 10 unwashed. An unloading section 117 is provided at the unloading port 114, for unloading the substrate 10 washed. The roller conveyer 115 extends from the loading section 116 to the unloading section 117.

The bottom of the washing vessel 112 has a pure water supply port 118 for supplying, for example, pure water W. The pure water port 118 is connected to a pure water source (not shown). Furthermore, an ultrasonic oscillator 119 (output 0.2 to 1.0 W/cm²) is provided on the inner bottom of the washing vessel 112.

A plurality of rotating brushes 120 and high-pressure air nozzles 121 are arranged above the roller conveyer 115. The rotation brush 120 comprises a rotation shaft 120a rotated by the rotation drive mechanism (not shown) and a nylon bristle 120b planted around the rotation shaft 120a and configured in the roll form.

The rotation brush 120 is provided for removing particles such as debris and burr remaining inside the

scribe line 54, by rubbing the substrate 10 and the
scribe line 54 with the tip of the bristle 120b onto.
To the portion rubbed and scribed by the rotation brush
120, high-pressure air is applied from the high
5 pressure air nozzle 121, thereby blowing the particles
away.

Furthermore, an air knife 122 is provided at the
unloading port 114 of the washing vessel 112, for
blowing pure water W and particles from the upper and
10 lower surfaces of the substrate 10.

Note that the purity of the water present in the
pure water supply source or at an output port of a pure
water producing unit is as follows:

Resistivity: 16-18 M Ω · cm (25°C)

15 The number of fine particles of 0.2 μ m or more:
100-150/ml

The number of viable bacteria: 0-10/ml

Organic material: 0.5 to 1.0 ppm.

As shown in FIGS. 8 and 9, an air blower mechanism
20 123 is provided in the unloading section 117 of the
washing vessel 112, for blowing a high pressure air to
an outer peripheral portion 10a of the substrate 10 to
be transferred by the roller conveyer 115.

The air blower mechanism 123 has a nozzle main
25 body 125. The body 125 has the same rectangular frame
form as the outer peripheral portion 10a of the
substrate 10 and has an air passage 124 inside. The

lower surface of the nozzle main body 125 has a plurality of nozzle holes 126 for spraying high pressure air to the outer peripheral portion 10a of the substrate 10.

5 The air blower mechanism 123 is provided above the substrate 10 placed on the roller conveyer 115. The air passage 124 is connected to a high pressure air source (not shown) by the air supply pipe 127.

10 How the substrate 10 is washed by the washing apparatus mentioned above will be described. Pure water W is supplied via the pure water supply port 118 to the washing vessel 112. When the pure water W reaches the level of the loading port 113 and the unloading port 114, it water W starts flowing out
15 through the loading port 113 and the unloading port 114. Therefore, the level of the pure water W in the washing vessel 112 remains constant. When power is supplied to the ultrasonic oscillator 119, ultrasonic vibration is transmitted to the pure water W.

20 When the substrate 10 is mounted on the roller conveyer 115 of the unloading section 116, the substrate 10 is transferred toward the loading port 113. When the substrate 10 is moved into the pure water W of the washing vessel 112 by the roller conveyer 115,
25 particles such as debris and burr are removed from the scribe line 54 of the substrate 10. This is because the pure water W is ultrasonically vibrated. The

particles removed are discharged along with the
flowing-out water or precipitated in the pure water W.
Therefore, no particles are attached again to the
substrate 10. It is therefore possible to effectively
5 reduce the contamination of the washing vessel 112 with
particles.

The substrate 10 is washed while being transferred.
Therefore, a plurality of substrates 10 are
continuously washed. Furthermore, the entire surface
10 of the substrate can be uniformly and ultrasonically
vibrated since the substrate 10 moves above the
ultrasonic oscillator 119.

The washed substrate 10 is unloaded from the
unloading port 114 of the washing vessel 112 to the
15 unloading section 117. The pure water W and the
particles are removed from the upper and the lower
surfaces of the substrate 10 unloaded from the
unloading port 114 as the high pressure air is blown
from the air knife 122. The substrate 10 can be
20 continuously washed and dried.

When the substrate 10 washed is conveyed to
the unloading section 117 by the roller conveyer 115,
high pressure air is blown to the substrate 10 from
the blow nozzle holes 126 of the air blow mechanism
25 123. The nozzle main body 125 has the same rectangular
frame form as the outer peripheral portion of the
substrate 10.

Since the high pressure air is strongly blown to the periphery 10a of the substrate 10, the water drops can be removed from the outer periphery 10a of the substrate 10, i.e., four sides thereof.

5 The high pressure air can be blown to the periphery 10a of the substrate 10, while the substrate 10 is being transferred by the roller conveyer 115. When the substrate 10 faces the air blower mechanism 123, the roller conveyer 115 is stopped in a stop B
10 zone shown in FIG. 8. The high pressure air can therefore be intensively blown to the periphery 10a of the substrate 10.

 Note that the air blower mechanism 123 (not shown) may be moved for a predetermined time in synchronism
15 with the movement of the substrate 10 transferred by the roller conveyer 115.

FIG. 10 shows a modified example of the air blower mechanism 128 according to a third embodiment.

 At the unloading section 117 of the washing vessel
20 112, upper-stage pulleys 130a, 130b, 130c are provided for a first corner portion 129a, a second corner portion 129b, and a third corner portion 129c, respectively. An upper-stage endless belt 131 is wrapped around these upper-stage pulleys 130a,
25 130b, 130c.

 Lower-stage pulleys 132a, 132b, 132c are provided respectively at the portions facing the first corner

portion 129a, a fourth corner portion 129d and the third corner portion 129c. A lower-stage endless belt 133 is wrapped around the lower-stage pulleys 132a, 132b, 132c.

5 The upper-stage pulley 130a and the lower-stage pulley 132a, which are provided at the first corner portion 129a, are supported coaxial with the upper-stage pulley 130c and the lower stage pulley 132c which are provided at the third corner portion 129c. A motor
10 134 is connected to the shaft of the upper-stage pulley 130a and the lower-stage pulley 132a, both provided at the first corner portion 129a.

 The air applying nozzles 135a and 135b are attached respectively to parts of the upper stage
15 endless belt 131 and the lower stage endless belt 133. The air applying nozzles 135a and 135b are connected to a high pressure air supply source.

 Since the air blower mechanism 128 is thus constructed, the upper-stage endless belt 131 and the
20 lower-stage endless belt 133 are moved in the directions indicated by arrows, respectively, when the upper pulley 130a and the lower pulley 132a are rotated by the rotation of the motor 134.

 Therefore, the air spray nozzle 135a moves along
25 the two sides of the substrate 10, which define the second corner portion 129b of the substrate 10. The air applying nozzle 135b moves along the two sides of

the substrate 10, which define the fourth corner portion 129d of the substrate 10. When a high-pressure air is blown from the air applying nozzles 135a and 135b, the high-pressure air is blown intensively toward the periphery 10a of the substrate 10, i.e., the four side surfaces thereof. It is therefore possible to blow water drops from the periphery 10a of the substrate 10.

The high pressure air is blown to the periphery 10a of the substrate (i.e., the four side surfaces thereof) while the substrate 10 is transferred by the roller conveyer 115. Alternatively, the air can be blown intensively to the periphery 10a of the substrate 10 by stopping the roller conveyer 115 at the stop zone B when the substrate 10 faces the air blower mechanism 123.

In the third embodiment, the air applying nozzles 135a and 135b are moved along the periphery 10a of the substrate 10 (i.e., the four side surfaces) by the pulleys and the endless belts. As the mechanism for driving the nozzles 135a and 135b, a ball-screw mechanism and a linear motor may be used. Nonetheless, the drive mechanism is not limited to this type.

In the second and third embodiments, the roller conveyer 115 is used to transport the substrate 10. The substrate may be transferred by a water-permeable endless belt made in the form of a mesh or a ladder.

The washing liquid is not limited to pure water W. Tap water or a chemical washing liquid may be used. The chemical washing liquid used may be water containing a detergent or organic solvent such as acetone, methanol, ethanol, trichloroethylene or Freon.

In the second and third embodiments shown in FIGS. 7 to 10, a substrate is washed which has, on one surface, a transparent conducting film with a scribe line formed by a laser beam. The substrate to be washed is not limited to this. The washing apparatuses according to the second and third embodiments can wash a substrate which has a semiconductor film and a rear surface electrode successively formed on a transparent conducting film and scribed by a laser beam.

The air blower mechanisms of the second and third embodiments may be arranged at downstream of the liquid removing section 2 of the first embodiment. With this arrangement, the washing liquid can be removed without fail even if the washing liquid remains on the periphery of the substrate after the substrate is dried in the liquid removing section 2.

FIGS. 11 and 12 show a liquid removing section 210 according to a fourth embodiment which can be used in place of the liquid removing section 2 of the first embodiment and the water removing air knife 122 of the second embodiment.

As shown in FIG. 11, the substrate 10 is washed,

after the transparent conducting film 51, semiconductor film 52, or rear surface electrode film 53 is laser-scribed. The substrate 10 is transferred to the liquid removing section 210 by the transfer roller 206, with
5 the scribe lines 55 (only some of the scribe lines are shown in FIG. 11) arranged perpendicular to the transfer direction indicated by an arrow X.

In the liquid removing section 210, three air knives 207a, 207b and 207c are arranged in the order
10 mentioned, from the upper portion to the lower portion. The air knives incline to the direction perpendicular to the substrate transfer direction X. In other words, they cover the substrate 10 over the entire width thereof.

As shown in FIG. 11, the distance D from one end
15 of the air knife 207a to the other end of the air knife 207c along the substrate transfer direction exceeds interval R of adjacent transfer rollers 206. Furthermore, the air knives incline more to the
20 direction perpendicular to the substrate transfer than in the case where a single knife is used.

The adjacent air knives (207a and 207b, or 207b and 207c in FIG. 11) are arranged with their most close end portions spaced apart from each other in the
25 substrate transfer direction and overlapping in the direction perpendicular to the substrate transfer direction. More specifically, as shown in FIG. 11, the

lower end of the air knife 207a is spaced apart from the upper end of the air knife 207b at an interval S in the substrate transfer direction. Furthermore, the lower end of the air knife 207a and the upper end of the air knife 207b overlap as shown by symbol L in FIG. 11. Liquid is removed by blowing compressed air to the substrate 10 from the slit nozzles 208, each extending over entire length of air knives 207a, 207b and 207c in the direction indicated by an arrow P in FIG. 11.

In this embodiment, three air knives 207a, 207b and 207c are arranged in excess of the interval R between the adjacent transfer rollers 206 and greatly inclined to the direction perpendicular to the substrate transfer direction. Furthermore, the overlapping portion L extends in the direction perpendicular to the substrate transfer direction. With this arrangement, compressed air can be reliably blown to the region corresponding to the interval R of the transfer roller 206. Therefore, liquid can be removed from the substrate 10 sufficiently.

Since the air knife is greatly inclined, a sufficient force is generated to blow away the washing liquid from the substrate 10 in the direction perpendicular to the substrate transfer direction.

The washing liquid is first pushed away through grooves of the scribe lines 55 by the compressed air

applied from the nozzle 208 of the air knife 207a. When the substrate 10 reaches the mid portion (interval S) between the air knife 207a and the air knife 207b along the substrate transfer direction, the compressed air is no longer applied to the washing liquid. The compressed air is not applied to the washing liquid for a short period of time, and no force is applied to the washing liquid for this period.

However, right before the washing liquid starts flowing reversely, the compressed air applied from the nozzle 208 of the air knife 207b blows the washing liquid through the grooves of the scribe lines 55. The liquid is blown in a similar manner by the air knives 207b and 207c.

When the compressed air is applied, the washing liquid forms waves in the grooves of the scribe lines 55. The waves are not so high. Therefore, when the waves become low in the middle region (interval S) between the air knives, not breaking or scattering, the washing liquid is made to flow again, by the compressed air blown from the next air knife. With this mechanism, the washing liquid is successfully removed from the substrate 10.

It is possible to improve the photovoltaic conversion efficiency of the photovoltaic module, because the waves of the particle-containing washing liquid do not break to wet the region from which water

has been completely removed.

The photovoltaic modules manufactured by using the substrate 10 washed in the method according to this embodiment were tested for current/voltage characteristics by using 1.5 solar simulator ($AM=1.5$, 100 mW/cm^2). As a result, the fill factor (FF) was 67%. On the other hand, the photovoltaic module manufactured by using the substrate 10 washed by a conventional method had a fill factor (FF) of 65%. Hence, the washing method of this embodiment is effective in improving the photovoltaic conversion efficiency of the photovoltaic module.

"AM" used herein stands for "Air Mass," which indicates a solar spectrum, and more specifically, the thickness of the atmospheric layer through which a solar light passes. For example, AM is 0 in the space and 1 right at the equator.

"FF" used herein stands for "Fill Factor." The maximum value of $V \times I$ on the VI curve of a photovoltaic module is denoted by "Pmax." FF is a value obtained by dividing Pmax by a product of multiplying an open circuit voltage (Voc) and short circuit current (Isc).

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments

shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents."

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232